

# MARKS PRYOR

MARKING TECHNOLOGY

**Compact and  
Lightweight**

**Robust and  
Durable**

**Specially  
Engraved  
Character  
Wheels**

**Wheel Positively  
Locked in  
Position by a  
Securing Pin**

**Small Frame  
Supplied with a  
Range of Shanks  
to Fit Standard  
Marking  
Machines**

**Strict Tolerances  
and Positive  
Character  
Alignment**




INTELLIGENT MARKING SOLUTIONS

# Numbering Head Manual Indexing

Unique compact design makes this unit a complete ready to use tool. Marked impressions are perfectly aligned, uniformly deep, evenly spaced-part after part. Low set up time, easy operation, robust construction gives high output rates at low cost.

## Key Features:

- 7 Standard Character sizes form 1.5 mm to 6 mm
- 1 to 14 wheel units available as standard
- Marking Wheels can be rotated to any given position - a complete inscription can be changed in seconds



## Special Features:

The security pin not only fastens the wheels in position, but also transmits the compressive load in the body of the tool, directly to the point of impact.



*Available on request*

- *Special calligraphy and 10 characters per wheel in any desired combination*
- *Bigger character size up to 12 mm*
- *Machine Numerator suitable for use on a press*

[www.markspryor.com](http://www.markspryor.com)

# Specification Details

Marks Pryor's range of Standard Numberers, designed for simple application of indent marking. Quick and easy to use hand numberers are suitable for marking most metal, many plastics and other materials. For use by hand and hammer or in most types of marking machines.

Standard wheels have sharp faced characters, 0-9 (inclusive) with one blank station. Allowing fast and simple character setting - ideal for random changing inscriptions and batch marking. Special wheels can be supplied to mark logos, symbols and letters. Characters forms can be sharp faced, flat faced, minstress, or dotstress.

Styles can be condensed or broad standard style or to any special character style. Concave and convex characters can also be provided.

## Inscription / No. Characters

The chart below shows the actual lengths for the number of wheels and character size required using standard style and spacing.

Small character sizes are supplied with our small frame supplied with interchangeable steel shanks to fit a variety of machines or for hand use. Larger sizes (3 mm) are supplied in a one piece frame for hand use only.

Using condensed style characters the next size up can be used, without changing the overall length of inscription from that shown for the smaller size, for example 3.0 mm condensed characters will give the same overall length as 2.5 mm standard.

The Seven Stock Sizes are Marked in Blue, Other Sizes shown can be Quickly Supplied

Size	Number of Wheels														Frame
mm	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
1.5	1.5	3.0	4.5	6.0	7.5	9.0	10.5	12.0	13.5	15.0	17.5	18.0	19.5	21.0	Small
2.0	2.0	4.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0					
2.5	2.5	5.0	7.5	10.0	12.5	15.0	17.5	20.0							
3.0	3.0	6.0	9.0	12.0	15.0	18.0	21.0								
4.0	4.0	8.0	12.0	16.0	20.0	24.0	28.0	32.0	36.0	40.0					
5.0	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0							Large
6.0	6.0	12.0	18.0	24.0	30.0	36.0	42.0								

Any Special Number outside the above range can be considered



AN ISO 9001-2008  
COMPANY



QAC / R81 / 1520

## MARKS PRYOR MARKING TECHNOLOGY PVT. LTD.

### CORPORATE OFFICE & WORKS

Regd. Off.: Gat No. 135, Pirangut, Tal. Mulshi, Dist. Pune - 412 108. (M.S.) India.

Tel.: +91-20-66743300 / 66743301 Fax: +91-20-66743327, e-mail : info@markspryor.com

### BRANCHES

- New Delhi • Mumbai • Bangalore • Ahmedabad • Chennai
- Coimbtore • Kolkata • Jamshedpur • Indore

[www.markspryor.com](http://www.markspryor.com)